



**GLOBAL POSITIONING SYSTEM (GPS)
PERFORMANCE**

JULY TO SEPTEMBER 2017

QUARTERLY REPORT

	Name – Responsibility	Date	Signature
Prepared by	M Pattinson (NSL)	16/10/17	
Checked by	L Banfield (NSL)	16/10/17	
Authorised by	M Dumville (NSL)	16/10/17	

Total Pages: 36

Change Record

Issue / Rev.	Date	§ : Change Record	Authors
1.A	16/10/17	First version delivered to CAA for review and comment	M Pattinson

Table of Contents

1 INTRODUCTION.....	6
1.1 Purpose of Document	6
1.2 Document Overview.....	6
1.3 References.....	7
1.3.1 Applicable Documents	7
1.3.2 Reference Documents	7
1.4 Acronyms.....	7
2 INTRODUCTION.....	9
2.1 Purpose.....	9
2.2 Performance Specification and Definitions	9
2.3 Methodology	12
2.4 Assumptions	16
3 SPS PERFORMANCE	18
3.1 Baseline 24-Slot Constellation	18
3.2 SPS SIS Accuracy	18
3.3 SPS SIS Integrity	21
3.4 SPS SIS Continuity.....	21
3.5 SPS SIS Availability.....	22
3.6 PDOP Availability	23
3.7 Position Service Availability.....	24
3.8 Positioning Accuracy.....	25
4 NANU ANALYSIS.....	28
5 CONCLUSIONS.....	31
6 APPENDIX A: GEOMAGNETIC DATA	34

List of Figures

Figure 2-1: Leica SmartNet Network.....	13
Figure 2-2: Location of IGS Hert Site.....	14
Figure 3-1: Constellation URE (95%) for Reporting Period.....	19
Figure 3-2: Constellation RMS URE for Reporting Period.....	19
Figure 3-3: Daily PDOP Availability in the Reporting Period.....	23
Figure 3-4: Daily Maximum PDOP Value in the Reporting Period.....	24
Figure 3-5: Daily Horizontal Service Availability Values for Reporting Period.....	25
Figure 3-6: Daily Vertical Service Availability Values for Reporting Period.....	25
Figure 3-7: Daily Horizontal Position Accuracy (95%) for Reporting Period.....	26
Figure 3-8: Daily Vertical Position Accuracy (95%) for Reporting Period.....	26
Figure 3-9: Daily Horizontal Position Accuracy (99.99%) for Reporting Period.....	27
Figure 3-10: Daily Vertical Position Accuracy (99.99%) for Reporting Period.....	27
Figure 6-1: K-Index Values at Lerwick during Reporting Period.....	34
Figure 6-2: K-Index Values at Eskdalemuir during Reporting Period.....	35
Figure 6-3: K-Index Values at Hartland during Reporting Period.....	35

List of Tables

Table 1-1: Applicable Documents	7
Table 1-2: Reference Documents	7
Table 1-3: Acronyms and Abbreviations	8
Table 2-1: SPS Criteria and Specifications	11
Table 3-1: Baseline constellation in the Period 1 st July to 18 th August 2017	18
Table 3-1: Baseline constellation in the Period 19 th August to 30 th September 2017	18
Table 3-2: Range Error Statistics for Reporting Period	20
Table 4-1: Summary of Forecast Scheduled Outages	28
Table 4-2: Summary of Actual Scheduled Outages	28
Table 4-3: Summary of Cancelled Outages	29
Table 4-4: Summary of Forecast and Actual Unscheduled Outages.....	29
Table 4-5: Summary of NANU Statistics for Monitoring Period	29
Table 5-1: Summary of Performance	32

1 INTRODUCTION

1.1 Purpose of Document

This document presents the results of the GPS SPS performance assessment for the period of 1 July 2017 to 30 September 2017. The objectives of the study are to compare the measured performance against US DoD SPS performance specification [RD.1], covering the following parameters [AD.1]:

- SPS SiS Accuracy,
- SPS SiS Integrity,
- SPS SiS Continuity,
- SPS SiS Availability,
- PDOP Availability,
- SPS Position Service Availability and
- SPS Position Service Accuracy.

It also includes NANU analysis and geomagnetic activity.

The performance is analysed using raw data recorded at the Ordnance Survey site LEEK, in the central UK.

1.2 Document Overview

This document is arranged in the following sections:

- **Section 1**, the current section, describes the purpose, scope and structure of the document and lists the reference documents.
- **Section 2** gives an introduction to the activity, including performance specification and assessment methodology and assumptions;
- **Section 3** contains an assessment of performance against GPS SPS performance standards;
- **Section 4** provides an analysis of the NANUs;
- **Section 5** contains the conclusions;
- **Section 6** (Appendix A) provides the geomagnetic activity data.

1.3 References

1.3.1 Applicable Documents

Ref.	Document title	Document reference	Issue	Date
AD.1	THE PROVISION OF MONITORING AND ANALYSIS OF GPS SIGNALS IN SPACE –	CONTRACT NO. 1762 (AMENDMENT NO. 5)	-	03/01/17

Table 1-1: Applicable Documents

1.3.2 Reference Documents

Ref.	Document title	Document reference	Issue	Date
RD.1	Global Positioning System Standard Positioning Service Performance Standard	GPS SPS	4 th Edition	Sept 2008
RD.2	Global Positioning System (GPS) Civil Monitoring Performance Specification	DOT-VNTSC-FAA-09-08	-	April 30 th 2009
RD.3	The International GNSS Service in a changing landscape of Global Navigation Satellite Systems	Journal of Geodesy 83: 191-198		2009
RD.4	Reference Set of Parameters for RAIM Availability Simulations', EUROCAE WG-62	-	-	8-9 July 2003

Table 1-2: Reference Documents

1.4 Acronyms

Acronym	Organisation
AOD	Age Of Data
CAA	Civil Aviation Authority
GNSS	Global Navigation Satellite System
GPS	Global Positioning System
HDOP	Horizontal Dilution Of Precision
IGS	International GNSS Service
NANU	Notice Advisory to Navstar Users
NOTAM	Notice To Airmen

Acronym	Organisation
NSL	Nottingham Scientific Ltd
PDOP	Position Dilution Of Precision
RAIM	Receiver Autonomous Integrity Monitoring
SIS	Signal In Space
SPS	Standard Positioning Service
TTA	Time To Alarm
UERE	User Equivalent Range Error
URA	User Range Accuracy
URE	User Range Error
VDOP	Vertical Dilution Of Precision

Table 1-3: Acronyms and Abbreviations

2 INTRODUCTION

2.1 Purpose

The purpose of the performance monitoring activity is to collect and analyse data on the performance of the GPS Signal in Space (SIS) [AD.1]. For this report, the applicable requirements are defined in the Global Positioning System Standard Positioning Service Performance Standard (GPS SPS PS), approved by the US Department of Defence [RD.1].

2.2 Performance Specification and Definitions

The applicable performance specifications for the Standard Positioning Service [RD. 1] are as follows:

Criteria	Specifications
SPS SIS Accuracy	<p>The User Range Error (URE) for any healthy satellite for Single-Frequency C/A-Code:</p> <ul style="list-style-type: none"> • ≤ 7.8 m 95% Global Average URE during Normal Operations over all age of data (AODs) • ≤ 6.0m 95% Global Average URE during Normal Operations at Zero AOD • ≤ 12.8 m 95% Global Average URE during Normal Operations at Any AOD • ≤ 30 m 99.94% Global Average URE during Normal Operations over one year period • ≤ 30 m 99.79% Worst Case Single Point Average URE during Normal Operations over one year period • ≤ 388 m 95% Global Average URE during Extended Operations after 14 Days without Upload. <p>The User Range Rate Error (URRE) for Single-Frequency C/A-Code:</p> <p>≤ 0.006 m/sec 95% Global Average URRE over any 3-second interval during Normal Operations at Any AOD</p> <p>The User Range Acceleration Error (URAE) for Single-Frequency C/A-Code:</p> <p>≤ 0.002 m/sec/sec 95% Global Average URAE over any 3-second interval during Normal Operations at Any AOD</p> <p>The UTC Offset Error for Single-Frequency C/A-Code:</p> <p>≤ 40 nsec 95% Global Average UTCOE during Normal Operations at Any AOD</p>

Criteria	Specifications
SPS SIS Integrity	<p>The SIS Integrity for Single-Frequency C/A-Code:</p> <ul style="list-style-type: none"> • $\leq 1 \times 10^{-5}$ Probability Over Any Hour of the SPS SIS Instantaneous URE Exceeding the NTE Tolerance Without a Timely Alert during Normal Operations <p>The UTCOE Integrity for Single-Frequency C/A-Code:</p> <ul style="list-style-type: none"> • $\leq 1 \times 10^{-5}$ Probability Over Any Hour of the SPS SIS Instantaneous UTCOE Exceeding the NTE Tolerance Without a Timely Alert during Normal Operations
SPS SIS Continuity	<p>SPS SIS Unscheduled Failure Interruption Continuity</p> <ul style="list-style-type: none"> • ≥ 0.9998 Probability Over Any Hour of Not Losing the SPS SIS Availability from a Slot Due to Unscheduled Interruption • Given that the SPS SIS is available from the slot at the start of the hour
SPS SIS Availability	<p>SPS SIS Per-Slot Availability</p> <ul style="list-style-type: none"> • ≥ 0.957 Probability that a Slot in the Baseline 24-Slot Configuration will be Occupied by a Satellite Broadcasting a Healthy SPS SIS • ≥ 0.957 Probability that a Slot in the Expanded Configuration will be Occupied by a Pair of Satellites Each Broadcasting a Healthy SPS SIS <p>SPS SIS Constellation Availability</p> <ul style="list-style-type: none"> • ≥ 0.98 Probability that at least 21 Slots out of the 24 Slots will be Occupied Either by a Satellite Broadcasting a Healthy SPS SIS in the Baseline 24-Slot Configuration or by a Pair of Satellites Each Broadcasting a Healthy SPS SIS in the Expanded Slot Configuration • ≥ 0.99999 Probability that at least 20 Slots out of the 24 Slots will be occupied either by a Satellite Broadcasting a Healthy SPS SIS in the Baseline 24-Slot Configuration or by a Pair of Satellites Each Broadcasting a Healthy SPS SIS in the Expanded Slot Configuration. • ≥ 0.95 Probability that the Constellation will have at least 24 Operational Satellites regardless of Whether Those Operational Satellites are Located in Slots or Not.
PDOP Availability	<ul style="list-style-type: none"> • $\geq 98\%$ global Position Dilution of Precision (PDOP) of 6 or less • $\geq 88\%$ worst site PDOP of 6 or less
SPS Position Service Availability	<ul style="list-style-type: none"> • $\geq 99\%$ Horizontal Service Availability average location • $\geq 90\%$ Horizontal Service Availability worst-case location • $\geq 99\%$ Vertical Service Availability average location • $\geq 90\%$ Vertical Service Availability worst-case location

Criteria	Specifications
	With 17 m horizontal and 37 m vertical (SIS only) 95% threshold over 24hours
Positioning Accuracy	<ul style="list-style-type: none"> • ≤ 9 meters 95% All-in-View Global Average Horizontal Error (SIS Only) • ≤ 17 meters 95% All-in-View worst site Horizontal Error (SIS Only) • ≤ 15 meters 95% All-in-View Global Average Vertical Error (SIS Only) • ≤ 37 meters 95% All-in-View worst site Vertical Error (SIS Only) • ≤ 40 nanoseconds time transfer error 95% of time (SIS Only) for Time Transfer Domain Accuracy

Table 2-1: SPS Criteria and Specifications

The definitions for each of the criteria and the methodology used for assessment are given below. As well as the GPS SPS [RD.1], the GPS civil monitoring performance specification [RD.2] has also been used to help define the methodology for the assessment.

SPS SIS Accuracy

The SPS SIS accuracy is described in two statistical ways; one way is as the 95th percentile (95%) SPS SIS user range error (URE) at a specified age of data (AOD), the other is as the 95% SPS SIS URE over all AODs. With either statistical expression, the SPS SIS accuracy is also known as the SPS SIS pseudorange accuracy. In this context, “pseudorange” means the full pseudorange data set (i.e., the matched combination of a corrected pseudorange measurement and a pseudorange origin, or equivalently the matched combination of a raw pseudorange measurement and the associated NAV data).

Other accuracy-related SPS SIS performance parameters include the SPS SIS pseudorange rate (velocity) accuracy defined as the 95% SPS SIS pseudorange rate error over all AODs and the SPS SIS pseudorange acceleration (rate rate) accuracy defined as the 95% SPS SIS pseudorange acceleration error over all AODs. These values are not monitored as part of this performance monitoring contract.

SPS SIS Integrity

The SPS SIS integrity is defined as the trust which can be placed in the correctness of the information provided by the SPS SIS. SPS SIS integrity includes the ability of the SPS SIS to provide timely alerts to receivers when the SPS SIS should not be used for positioning or timing. The SPS SIS should not be used when it is providing misleading signal-in-space information (MSI), where the threshold for “misleading” is a not-to-exceed (NTE) tolerance on the SIS URE. For this SPS PS, the four components of integrity are the probability of a major service failure, the time to alert, the SIS URE NTE tolerance, and the alert (either one or the other of two types of alerts).

- **Probability of a Major Service Failure.** The probability of a major service failure for the SPS SIS is defined to be the probability that the SPS SIS instantaneous URE exceeds the SIS URE NTE tolerance (i.e., MSI) without a timely alert being issued (i.e., unalerted MSI [UMSI]). Alerts generically include both alarms and warnings.
- **Time to Alert.** The time to alert (TTA) for the SPS SIS is defined to be the time from the onset of MSI until an alert (alarm or warning) indication arrives at the receiver's antenna. Real-time alert information broadcast as part of the NAV message data is

defined to arrive at the receiver's antenna at the end of the NAV message subframe which contains that particular piece of real-time alert information.

- **SIS URE NTE Tolerance.** The SPS SIS URE NTE tolerance for a healthy SPS SIS is defined to be 4.42 times the upper bound on the URA value corresponding to the URA index "N" currently broadcast by the satellite. The SIS URE NTE tolerance for a marginal SPS SIS is not defined and there is no SIS URE NTE tolerance for an unhealthy SPS SIS.

SPS SIS Continuity

The SPS SIS continuity for a healthy SPS SIS is the probability that the SPS SIS will continue to be healthy without unscheduled interruption over a specified time interval. Scheduled interruptions which are announced at least 48 hours in advance do not contribute to a loss of continuity. Scheduled SPS SIS interruptions are announced by way of the Control Segment issuing a "Notice Advisory to Navstar Users" (NANU). NANUs are similar to the "Notices to Airmen" (NOTAMs) issued regarding scheduled interruptions of ground-based air navigation aids. OCS internal procedures are to issue NANUs for scheduled interruptions at least 96 hours in advance.

SPS SIS Availability

The SPS SIS availability is the probability that the slots in the GPS constellation will be occupied by satellites transmitting a trackable and healthy SPS SIS. For this SPS Performance Standard, there are two components of availability as follows:

- **Per-Slot Availability.** The fraction of time that a slot in the GPS constellation will be occupied by a satellite that is transmitting a trackable and healthy SPS SIS.
- **Constellation Availability.** The fraction of time that a specified number of slots in the GPS constellation

PDOP Availability

PDOP availability is defined as the percentage of time over a specified time interval that the predicted PDOP is less than a specified value for any point within the service volume [RD.1].

Position Service Availability

Position service availability is defined as the percentage of time over a specified time interval that the position accuracy is less than a specified value for any point within the service volume [RD.1].

Positioning Service Accuracy

Position service accuracy is defined as the statistical difference between position measurements and a surveyed benchmark for any point within the service volume over a specified time interval [RD.1].

2.3 Methodology

For the performance analysis in this report, raw GPS measurement data from reference stations has been analysed.

The primary source of data is the Ordnance Survey network of active stations in the UK. The Ordnance Survey of Great Britain operates a national GPS network of GPS receiver stations. The network consists of over 50 receivers that provide 24 hour availability of dual frequency GPS and GLONASS data. NSL has access to this data through the Leica SmartNet service, which provides data from the OS network, as well as sites in Ireland and

some additional dedicated Leica installations. This means that data from any of the sites in the UK can be used. The network is presented in Figure 2-1.




Figure 2-1: Leica SmartNet Network

As only a single site is required for the performance monitoring LEEK has been chosen as this is located centrally in the UK and has high data availability with few gaps. Therefore during this monitoring period the LEEK site is used as the main source of 1Hz data, and hence the performance statistics during this period are based on data from that site. In case there are problems with the data access from SmartNet, data from the Hert IGS site in the South of the UK can be used. The location of the site is shown in the following Google Earth plot.




Figure 2-2: Location of IGS Hert Site

The receiver is a Leica GRX1200GGPro geodetic receiver, connected to a LEIAT504GG antenna, which records dual frequency (L1 and L2) GPS and GLONASS measurements at 1Hz rate. The data files are accessed via ftp and are downloaded at NSL before processing with GISMO SW. The daily navigation message files for the Hers receiver at that site are also downloaded from the IGS ftp site and used to provide the navigation data [RD.3]. In addition to the raw data, NANU information is downloaded from the US Coast Guard Navigation Centre website (<http://www.navcen.uscg.gov/?pageName=gpsNanuInfo>). This provides information on the NANUs for scheduled and unscheduled outages during the monitoring period.

The methods for assessing of each of the requirements are described below.

SPS SIS Accuracy

SIS accuracy is assessed through processing and analysis of the raw measurement data. In order to compute the SIS accuracy, the measurements recorded at the GPS receiver are used to compute the instantaneous SIS errors. This is done by computing the difference between computed ranges (based on known receiver location and satellite position) and the corrected measurement, which has satellite and receiver clock biases, group delay, ionospheric and tropospheric errors removed. Once the SIS range errors for every satellite measurement on every epoch have been computed, the per-satellite statistics across the whole period, as well as daily statistics for all satellites combined, are generated.

SPS SIS Integrity

SIS accuracy is assessed through processing and analysis of the raw measurement data. The SIS integrity is assessed by comparing each instantaneous computed SIS error value

with a threshold value of $4.42 \times$ broadcast URA. The number of occasions where the instantaneous URE exceeds the threshold are counted and checked against the expected number of failures.

SPS SIS Continuity

SIS continuity is assessed through analysis of the broadcast navigation messages and the NANU archive. Firstly, the daily broadcast navigation messages are scanned in order to find the time periods for any satellites that do not have healthy navigation messages. These satellites and time periods are then matched against NANU information to see if the outages are scheduled or unscheduled.

The SIS continuity is computed for the baseline 24-slot constellation and is an average value over all slots. The total time that any satellites in the baseline constellation were unhealthy due to an unscheduled outage is divided by the total time in the analysis period and expressed as a percentage. Results are presented for the reporting period and, when available, for the previous year.

SPS SIS Availability

SIS availability is assessed through analysis of the broadcast navigation messages and the NANU archive. Firstly, the daily broadcast navigation messages are scanned in order to find the time periods for any satellites that do not have healthy navigation messages. These satellites and time periods are then matched against NANU information to see if the outages are scheduled or unscheduled.

The SIS availability is computed for the baseline 24-slot constellation as well as for the whole constellation and is an average value over all slots. At each epoch the number of healthy satellites (both in the baseline 24-slot constellation and in total) is counted. Then the following parameters are computed:

- Total time that there are less than 21 healthy satellites in the baseline constellation;
- Total time that there are less than 20 healthy satellites in the baseline constellation;
- Total time that there are less than 24 healthy satellites in the whole constellation.

These parameters are then divided by total time of the analysis and expressed as percentage values. Results are presented for the reporting period and, when available, for the previous year.

It should be noted that in case the baseline 24-slot constellation does not meet requirements, the analysis will be expanded to include pairs of satellites in the expanded slot constellation.

PDOP Availability

PDOP availability is assessed through processing and analysis of the raw measurement data. The PDOP availability is assessed by computing the PDOP for all satellites in view above 5 degrees at the GPS receiver at every epoch (1Hz rate). Each PDOP value is checked against the threshold value of 6 and any failures are counted. The numbers of failures on each day are then used to generate the daily availability value. A separate availability value for each day is computed.

Position Service Availability

Position service availability is assessed through processing and analysis of the raw measurement data. The derivation of the position service availability requirements of 17m

(95% horizontal accuracy) and 37m (95% vertical accuracy) for 99% of the time are explained a bit more in section B.3.1 of the GPS SPS [RD.1]. The requirement is based on fulfilling a 1-sigma UERE of 4m, HDOP of 2.1 and VDOP of 4.4. To check this requirement, the following approach is used:

- For each day, compute daily rms SIS error for all satellites combined. This is equivalent to the 1-sigma UERE in the description above;
- On each epoch, multiply daily rms SIS error by HDOP value to compute estimated horizontal accuracy due to SIS error;
- For each epoch, multiply daily rms SIS error by VDOP value to compute estimated vertical accuracy due to SIS error;
- Compute daily availability (%) of estimated horizontal accuracy < 8.5m (1-sigma);
- Compute daily availability (%) of estimated vertical accuracy < 18.5m (1-sigma).
- If daily availability of horizontal accuracy greater than the required threshold, the requirement for horizontal service accuracy is passed;
- If daily availability of vertical accuracy greater than the required threshold, the requirement for vertical service accuracy is passed.

Positioning Service Accuracy

In order to check the position service accuracy, the raw measurements recorded at the GPS receiver are used to compute a user position solution on every epoch (1Hz). The computed positions are then compared against the known position of the receiver in order to generate horizontal and vertical position errors. Statistics for 95% error value, 99.99% error value etc. are then computed separately for each day and checked against the thresholds.

2.4 Assumptions

For processing the raw data and generating the results the following assumptions are made:

- Single frequency (L1) processing with C/A code;
- 5 degree elevation mask used;
- Broadcast iono model (Klobuchar) used to remove ionospheric errors;
- RTCA trop model used to remove tropospheric errors;
- Weighted least squares RAIM algorithm used for RAIM prediction (protection level computation) and Fault Detection;
- Probability of missed detection = 0.001 and Probability of false alarm = 1×10^{-5} for RAIM computations;
- UERE budget (non-SIS components) used in position solution and for RAIM predictions are given below [RD.4]:

Elevation, degrees	Error, metres
5	7.48
10	6.64
15	5.92
20	5.31
30	4.31
40	3.57
50	3.06

Elevation, degrees	Error, metres
60	2.73
90	2.44

- The URA value from the broadcast navigation message is combined with the values in the table to form the total UERE for the observations.

As the actual monitoring is based on the measurements from one receiver the following points should be noted:

- Performance monitoring is local to the monitoring station with a coverage area defined by the correlation of the major error sources and the configuration of the constellation;
- The range domain errors contain the residuals of other error sources other than the SIS range errors; hence, the performance statistics generated are conservative.

3 SPS PERFORMANCE

3.1 Baseline 24-Slot Constellation

The SPS SIS performance standard is largely based on the GPS baseline 24-slot constellation, which consists of 24 slots in six orbital planes with four slots per plane. It is important to identify the baseline constellation to act as reference to subsequent data processing and analysis. The following tables show the satellite PRN in each slot for the baseline constellation for the period July to September 2017.

Slot	A1	A2	A3	A4	B1	B2	B3	B4	C1	C2	C3	C4
PRN	24	31	30	7	16	25	28	12	29	27	8	17
Slot	D1	D2	D3	D4	E1	E2	E3	E4	F1	F2	F3	F4
PRN	2	1	21	6	3	10	5	18	14	15	9	23

Table 3-1: Baseline constellation in the Period 1st July to 18th August 2017

Slot	A1	A2	A3	A4	B1	B2	B3	B4	C1	C2	C3	C4
PRN	24	31	30	7	16	25	28	12	29	27	8	17
Slot	D1	D2	D3	D4	E1	E2	E3	E4	F1	F2	F3	F4
PRN	2	1	21	6	3	10	5	18	32	15	9	23

Table 3-2: Baseline constellation in the Period 19th August to 30th September 2017

3.2 SPS SIS Accuracy

In addition to the specifications in Table 2-1, the Conditions and Constraints for SPS SIS URE Accuracy specification [RD.1] are:

- For any healthy SPS SIS
- Neglecting single-frequency ionospheric delay model errors
- Including group delay time correction (TGD) errors at L1
- Including inter-signal bias (P(Y)-code to C/A-code) errors at L1

The statistics presented here are based on the same sample rate for positioning (1Hz). It should be noted that the computed range errors (in addition to SIS errors) contain residual errors local to the monitoring antenna (multipath, tropospheric and ionospheric). The URE Accuracy (95th percentile) values of each satellite for the period July 1 to September 30 2017 are shown in the next figure.




Figure 3-1: Constellation URE (95%) for Reporting Period

It can be seen that the URE (95%) for all satellites is below the 7.8m threshold. The daily constellation RMS URE results in the period July to September 2017 and the 4m threshold are shown in the next figure. Note that ≤ 7.8 m 95% SPS SIS URE performance standard is equivalent to a ≤ 4.0 m RMS SPS SIS URE performance standard [RD.1]. This is also important for the position service availability assessment.




Figure 3-2: Constellation RMS URE for Reporting Period

It can be seen that the RMS values are below the threshold (4 metres) on all days.

As well as the 95% and rms URE statistics, additional URE statistics are computed, including mean, 1-sigma and maximum values. Although not strictly required for the performance specification, these values can be useful for anomaly investigation.

The range error statistics (in metres) for the period July 1 to September 30 2017 are given in the table below.

PRN	Range Error (mean)	Range Error (RMS)	1-sigma	Range Error (95%)	Range Error (max)	Number of Samples
1	0.32	1.24	1.20	2.66	5.58	2230806
2	1.03	1.39	0.93	2.52	4.60	2905015
3	-0.11	1.04	1.04	2.12	4.45	2313416
5	0.28	0.87	0.82	1.71	4.71	2627092
6	0.15	0.84	0.83	1.70	4.13	2766410
7	0.37	0.99	0.92	1.97	5.78	2681601
8	0.37	1.46	1.41	2.94	8.16	2575515
9	0.14	0.97	0.96	1.92	4.79	2505978
10	-0.28	0.96	0.92	1.80	4.52	2851924
11	0.69	1.51	1.34	3.10	6.20	2049517
12	0.41	1.12	1.04	2.18	4.13	2546664
13	0.40	0.98	0.89	1.93	5.17	2335639
14	0.57	1.19	1.04	2.30	4.76	2925115
15	0.23	0.92	0.89	1.80	4.55	2529870
16	0.43	1.02	0.93	1.98	4.61	2674966
17	0.50	1.19	1.08	2.43	5.26	2892295
18	0.41	0.91	0.81	1.81	5.38	2877001
19	1.31	1.63	0.96	3.14	7.45	2859648
20	1.03	1.35	0.88	2.58	5.04	2826004
21	0.70	1.13	0.89	2.21	4.42	2796911
22	1.47	1.88	1.16	3.72	6.61	2279791
23	0.27	0.99	0.95	1.90	5.27	2650521
24	0.59	1.71	1.60	3.53	6.39	2088981
25	0.83	1.33	1.04	2.53	4.16	2298471
26	-0.02	1.03	1.03	2.06	6.02	2590090
27	0.39	1.12	1.04	2.32	5.29	2391975
28	0.79	1.45	1.21	2.78	6.29	2883669
29	0.37	1.01	0.94	2.00	4.83	2655512
30	0.67	1.12	0.89	2.18	5.13	2669056
31	-0.09	0.96	0.95	1.90	4.71	2781108
32	-0.37	0.96	0.89	1.90	4.84	2880983

Table 3-3: Range Error Statistics for Reporting Period

Overall, the measured SIS accuracy is below the threshold values throughout the monitoring period.

3.3 SPS SIS Integrity

In addition to the specifications in Table 2-1, the Conditions and Constraints for SPS SIS Integrity performance [RD.1] are:

- For any healthy SPS SIS;
- SPS SIS URE NTE tolerance defined to be ± 4.42 times the upper bound on the URA value corresponding to the URA index "N" currently broadcast by the satellite;
- Given that the maximum SPS SIS instantaneous URE did not exceed the NTE tolerance at the start of the hour;
- Worst case for delayed alert is 6 hours;
- Neglecting single-frequency ionospheric delay model errors.

Based on the requirement of 1×10^{-5} /hr probability for misleading information, 92 day period and a 31 satellite constellation, the maximum number of events expected is 0.67.

On every epoch throughout the monitoring period, the instantaneous measured URE for each satellite has been compared against a threshold of 4.42 times the upper value of the URA index. The number of URE values above the threshold has been recorded and is checked against the expected number.

From the analysis there is one day that appeared to have a potential problem. This was on 12th September at 08:51:19 where there were apparent range errors of around 1000m metres on PRN07. This sort of error was also seen at other sites too for the same satellite and so this is not a local problem – it is a satellite problem. At this time there is an active unplanned outage (unscheduled NANU 2017099) and it seems that for most of this period there are no measurements to PRN07 (perhaps it is not transmitting) but for 11 seconds from 08:51:19 measurements do appear in the observation RINEX file with very large errors (~1km range error). Looking at the navigation messages there is no new message received with an UNHEALTHY status flag for some time after this, and so at the time of these observations there is no indication to the receiver that PRN07 is unhealthy and should not be used. In post-processing this causes position errors of 204m in horizontal and 185m in vertical, although such a fault is easily detected by the RAIM algorithm and the fault identified or the solution discarded. The actual impact on receivers that were providing real-time navigation solutions is difficult to say for sure because it will depend on whether the satellite was in view of the receiver for that short period, whether the receiver had a valid navigation message to use for that satellite, and whether or not the receiver applied a RAIM algorithm or other measurement checks to identify and remove faulty satellites. Nevertheless, it is clear there was a potential issue at this time.

3.4 SPS SIS Continuity

In addition to the specifications in Table 2-1, the Conditions and Constraints for SPS SIS Continuity performance [RD.1] are:

- Calculated as an average over all slots in the 24-slot constellation, normalized annually;
- Given that the SPS SIS is available from the slot at the start of the hour.

During this reporting period there were five unscheduled outages affecting the baseline constellation totalling 97.22 hrs. Therefore the continuity in this period was 99.82%, which is below the requirement of 99.98%.

For the previous rolling year, there have been eight unscheduled outages on the baseline constellation lasting for 106.48 hrs in total. This gives a continuity value for the year of 99.949%, which does not meet the performance standard.

3.5 SPS SIS Availability

In addition to the specifications in Table 2-1, the Conditions and Constraints for SPS SIS Availability performance [RD.1] are:

- Calculated as an average over all slots in the 24-slot constellation, normalized annually;
- Applies to satellites broadcasting a healthy SPS SIS which also satisfy the other performance standards in this SPS Performance Standard.

The total period (in this monitoring period) in which satellites from the baseline 24-satellite constellation broadcast an unhealthy SIS was 148.52 hours. This is equivalent to an average of 0.997 over all slots in the 24-slot constellation, and satisfies SPS SIS Per-slot Availability standard (≥ 0.957).

The minimum number of the baseline constellation satellites broadcasting healthy SPS SIS was 22, greater than the specifications of 20 and 21. Hence, performance during the monitoring period was measured at the 100% level, satisfying the Performance Standard as specified below.

- ≥ 0.98 Probability that at least 21 Slots out of the 24 Slots will be Occupied Either by a Satellite Broadcasting a Healthy SPS SIS in the Baseline 24-Slot Configuration or by a Pair of Satellites Each Broadcasting a Healthy SPS SIS in the Expanded Slot Configuration;
- ≥ 0.99999 Probability that at least 20 Slots out of the 24 Slots will be occupied either by a Satellite Broadcasting a Healthy SPS SIS in the Baseline 24-Slot Configuration or by a Pair of Satellites Each Broadcasting a Healthy SPS SIS in the Expanded Slot Configuration.

The minimum number of operational satellites broadcasting healthy messages in this reporting period was 29. This represents performance at the 100% level, satisfying the Performance Standard as specified below.

- ≥ 0.95 Probability that the Constellation has at least 24 operational satellites regardless of whether the operational satellites are located in the baseline slots.

For the previous rolling year, the total period in which satellites from the baseline 24-satellite constellation broadcast an unhealthy SIS was 227.83 hours. This is equivalent to an average of 0.999 over all slots in the 24-slot constellation, and satisfies SPS SIS Per-slot Availability standard (≥ 0.957).

The minimum number of the baseline constellation satellites broadcasting healthy SPS SIS was 22, greater than the specifications of 20 and 21, and the minimum number of operational satellites broadcasting healthy messages was 29. This means that all constellation availability requirements from the Performance Standard are met for the previous year.

3.6 PDOP Availability

In addition to the specifications in Table 2-1, the Conditions and Constraints for PDOP performance [RD.1] are:

- Defined for position solution meeting the representative user conditions and operating within the service volume over any 24-hour interval;
- Based on using only satellites transmitting standard code and indicating “healthy” in the broadcast navigation message.

The following plot shows the daily PDOP availability (PDOP < 6) calculated at the site for all healthy satellites above 5 degrees elevation during the period July 1 to September 30 2017.




Figure 3-3: Daily PDOP Availability in the Reporting Period

It can be seen that the daily PDOP availability values are all above the thresholds of 98% (global average) and 88% (worst site). Therefore the PDOP availability fulfils the requirements.

In addition, the daily mean and maximum PDOP values are displayed for the same period.




Figure 3-4: Daily Maximum PDOP Value in the Reporting Period

The daily PDOP values PDOP can be used to identify specific days that have different performance from the others. It can be seen is that the maximum PDOP is always well below the threshold of 6.

3.7 Position Service Availability

In addition to the specifications in Table 2-1, the Conditions and Constraints for Service Availability performance [RD.1] are:

- 17 meters horizontal (SIS only) 95% threshold;
- 37 meters vertical (SIS only) 95% threshold;
- Defined for position solution meeting representative user conditions and operating within the service volume over any 24-hour interval;
- Based on using only satellites transmitting standard code and indicating “healthy” in the broadcast navigation message.

The computation of these values is detailed in section 2.2.

The daily horizontal and vertical service availabilities for the period July 1 to September 30 2017 are shown in the following figures.




Figure 3-5: Daily Horizontal Service Availability Values for Reporting Period




Figure 3-6: Daily Vertical Service Availability Values for Reporting Period

These plots show the horizontal and vertical availability are well above the thresholds of 99% (global average) and 90% (worst site) for the reporting period. Therefore the position service availability fulfils the requirements.

3.8 Positioning Accuracy

In addition to the specifications in Table 2-1, the Conditions and Constraints for Positioning Accuracy performance [RD.1] are:

- Defined for position solution meeting the representative user conditions;

- Standard based on a measurement interval of 24 hours averaged over all points within the service volume.

For this monitoring activity it should be noted that the position accuracy is assessed through analysis of real data at a single point, rather than through service volume analysis. The daily horizontal and vertical accuracy values (95%) for the period July 1 to September 30 2017 are shown in the following figures.




Figure 3-7: Daily Horizontal Position Accuracy (95%) for Reporting Period




Figure 3-8: Daily Vertical Position Accuracy (95%) for Reporting Period

It can be seen that the daily horizontal accuracy values are all below the thresholds of 9m (global average) and 17m (worst site).

Also the daily vertical accuracy values are well below the thresholds of 15m (global average) and 37m (worst site).
In addition, the daily position accuracy values at the 99.99% level are shown for the same period.




Figure 3-9: Daily Horizontal Position Accuracy (99.99%) for Reporting Period




Figure 3-10: Daily Vertical Position Accuracy (99.99%) for Reporting Period

It can be seen that the 99.99% values generally follow the same pattern as the 95% values and are not significantly larger.

4 NANU ANALYSIS

NANU information is downloaded from the US Coast Guard Navigation Centre website (<http://www.navcen.uscg.gov/?pageName=gpsNanuInfo>). Summaries of the forecast and actual outages for scheduled and unscheduled events are given below. NANUs that affect the baseline constellation are highlighted in green.

NANU	PRN	Type	Start day	Start Time	Stop day	Stop time	Outage (hours)	Ref
2017062	2	FCSTDV	187	1755	188	555	12	D1
2017064	23	FCSTMX	192	2300	193	700	8	F4
2017065	5	FCSTMX	194	2100	195	500	8	E3
2017068	7	FCSTMX	199	2030	200	430	8	A4
2017072	25	FCSTDV	215	1605	216	405	12	B2
2017073	17	FCSTMX	220	2300	221	700	8	C4
2017074	15	FCSTMX	222	1400	222	2200	8	F2
2017077	31	FCSTMX	227	1300	227	2100	8	A2
2017078	2	FCSTMX	230	230	230	1030	8	D1
2017082	9	FCSTDV	230	800	230	2000	12	F3
2017085	29	FCSTMX	234	1930	235	330	8	C1
2017086	12	FCSTMX	236	530	236	1330	8	B4
2017087	9	FCSTDV	237	815	237	2015	12	F3
2017089	21	FCSTMX	241	1700	242	100	8	D3
2017090	5	FCSTDV	243	1915	244	715	12	E3
2017095	13	FCSTDV	250	1030	250	2230	12	F6
2017098	26	FCSTDV	262	1120	262	2320	12	B5

Table 4-1: Summary of Forecast Scheduled Outages

NANU	PRN	Type	Start day	Start Time	Stop day	Stop time	Outage (hours)	Ref
2017066	2	FCSTSUMM	187	1841	188	9	5.466667	2017062
2017067	23	FCSTSUMM	192	2345	193	220	2.583333	2017064
2017069	5	FCSTSUMM	194	2136	195	20	2.733333	2017065
2017071	7	FCSTSUMM	199	2127	200	327	6	2017068
2017075	25	FCSTSUMM	215	1614	215	2128	5.233333	2017072
2017076	17	FCSTSUMM	220	2345	221	335	3.833333	2017073
2017079	15	FCSTSUMM	222	1439	222	1752	3.216667	2017074
2017084	31	FCSTSUMM	227	1502	227	1720	2.3	2017077
2017088	2	FCSTSUMM	230	312	230	536	2.4	2017078
2017091	29	FCSTSUMM	234	2008	234	2221	2.216667	2017085
2017092	12	FCSTSUMM	236	613	236	835	2.366667	2017086
2017093	9	FCSTSUMM	237	847	237	1358	5.183333	2017087
2017094	21	FCSTSUMM	241	1738	241	2007	2.483333	2017089
2017096	5	FCSTSUMM	243	1956	244	113	5.283333	2017090
2017097	13	FCSTSUMM	250	1050	250	1757	7.116667	2017095

Table 4-2: Summary of Actual Scheduled Outages

NANU	PRN	Type	Start day	Start Time	Stop day	Stop time	Ref
2017083	9	FCSTCANC	230	800	NA	NA	2017082
2017107	26	FCSTCANC	262	1120	NA	NA	2017098

Table 4-3: Summary of Cancelled Outages

NANU	PRN	Type	Start day	Start Time	Stop day	Stop time	Outage (hours)	Ref
2017080	9	UNUSUFN	223	1059	NA	NA	NA	F3
2017081	9	UNUSABLE	223	1058	223	1341	2.7166667	2017080
2017099	7	UNUSUFN	255	626	NA	NA	NA	A4
2017100	7	UNUSABLE	255	625	255	1007	3.75	2017099
2017101	7	UNUSUFN	255	1342	NA	NA	NA	A4
2017104	7	UNUSABLE	255	1342	258	2009	78.45	2017101
2017102	1	UNUSUFN	257	21	NA	NA	NA	D2
2017103	1	UNUSABLE	257	21	257	926	9.0833333	2017102
2017105	25	UNUSUFN	260	1500	NA	NA	NA	B2
2017106	25	UNUSABLE	260	1500	260	1813	3.2166667	2017105

Table 4-4: Summary of Forecast and Actual Unscheduled Outages

The constellation availability and continuity figures for the baseline constellation, and for all satellites, based on the NANU information are shown in the following table.

	Q3 2017
hrs	2208
total forecast downtime (all)	164.00
total forecast downtime (baseline)	140.00
total actual scheduled downtime (all)	58.42
total actual scheduled downtime (baseline)	51.30
Scheduled satellite outage events (all)	17
Scheduled satellite outage events (baseline)	140
Unscheduled satellite outage events (all)	5
Unscheduled satellite outage events (baseline)	5
Total actual unscheduled downtime (all)	97.22
Total actual unscheduled downtime (baseline)	97.22
Total actual downtime (all)	155.63
Total actual downtime (baseline)	148.52
Availability (all)	99.773
Availability (baseline)	99.720
Continuity (baseline)	99.817

Table 4-5: Summary of NANU Statistics for Monitoring Period

From the results it can be seen that the forecast downtime was greater than the actual downtime. Also, the actual scheduled downtime periods were within the time period described in the forecast NANUs.

There were five unscheduled outages in this period, all of which were on the baseline constellation and had a total outage time of 97.22 hrs.

From analysis of the broadcast navigation messages it can be seen that all occurrences of unhealthy satellites were linked with NANUs.

5 CONCLUSIONS

The following table summarises the measured performance against the specification.

Criteria	Specifications	Measured Performance	Passed
SPS SIS Accuracy	The User Range Error (URE) ≤ 7.8 m 95%	All SVs < 7.8m	Yes.
SPS SIS rms	≤ 4 m	All days <4m	Yes.
SPS SIS Integrity	The SIS Integrity $\leq 1 \times 10^{-5}$ Probability Over Any Hour (<0.7 events per quarter)	One day with large errors on PRN07	No
SPS SIS Continuity	≥ 0.9998 Probability Over Any Hour	99.82% (five unscheduled outages) 99.949% for rolling year	No, for both monitoring period and rolling year.
SPS SIS Availability	<p>SPS SIS Per-Slot Availability</p> <ul style="list-style-type: none"> ≥ 0.957 <p>SPS SIS Constellation Availability</p> <ul style="list-style-type: none"> ≥ 0.98 Probability that at least 21 Slots out of the 24 Slots will be healthy ≥ 0.99999 Probability that at least 20 Slots out of the 24 Slots will be healthy ≥ 0.95 Probability that the Constellation will have at least 24 Operational Satellites 	<p>1) 99.9% per-Slot Availability</p> <p>2) 100% Constellation Availability</p> <p>3) 100% probability that the number of operational satellite is larger than 24.</p>	Yes, for both monitoring period and rolling year.

Criteria	Specifications	Measured Performance	Passed
PDOP Availability	<ul style="list-style-type: none"> • $\geq 98\%$ global PDOP of 6 or less • $\geq 88\%$ worst site PDOP of 6 or less 	>99.8% availability on all days	Yes
SPS Position Service Availability	<ul style="list-style-type: none"> • $\geq 99\%$ Horizontal Service Availability average location • $\geq 90\%$ Horizontal Service Availability worst-case location • $\geq 99\%$ Vertical Service Availability average location • $\geq 90\%$ Vertical Service Availability worst-case location 	100% availability on all days	Yes
Positioning Accuracy	<ul style="list-style-type: none"> • ≤ 9 meters 95% All-in-View Global Average Horizontal Error (SIS Only) • ≤ 17 meters 95% All-in-View worst site Horizontal Error (SIS Only) • ≤ 15 meters 95% All-in-View Global Average Vertical Error (SIS Only) • ≤ 37 meters 95% All-in-View worst site Vertical Error (SIS Only) 	1) <3 metres 95% Horizontal Error at the site 2) <7 metres 95% Vertical Error at the site	Yes

Table 5-1: Summary of Performance

From the table it can be seen that the measured performance is within the required values for most requirements. The exceptions are the SIS continuity, where there were several long unplanned outages causing the continuity to fall below the requirement, and also potentially the SIS integrity requirement, where there appeared to be a short period where a signal with

large range errors was broadcast for PRN07 during an unplanned outage without a corresponding UNHEALTHY flag in the navigation message.

6 APPENDIX A: GEOMAGNETIC DATA

The solar activity during a particular period can be determined using the K index data provided by the British Geological Survey (BGS) in the UK. This data is available from http://www.geomag.bgs.ac.uk/data_service/data/magnetic_indices/k_indices.html.

The K index at each observatory summarises the geomagnetic activity by assigning an index value (in the range 0 – 9) to each 3-hr time interval. The index values are determined from the maximum range in H or D with allowance made for the normal (undisturbed) diurnal variation. The conversion from range to index value is made using a quasi-logarithmic scale, with the scale values dependent on the geomagnetic latitude of the observatory.

In general, the higher the K index the more active the Earth's magnetic field. K-index values of 5 or higher indicate geomagnetic storm level activity and index values of 7 or higher indicate a severe geomagnetic storm.

The geomagnetic activity is important to consider for GPS signals as geomagnetic storms may affect GPS performance, either by increasing the residual ionospheric delay errors in the position solution or by causing problems with tracking the satellite signals.

The following figures show the K-index values at 3 sites in the UK during the monitoring period. The figures are reproduced with the permission of the British Geological Survey ©NERC. All rights reserved.




Figure 6-1: K-Index Values at Lerwick during Reporting Period




Figure 6-2: K-Index Values at Eskdalemuir during Reporting Period




Figure 6-3: K-Index Values at Hartland during Reporting Period

It can be seen that during the monitoring period there are a few occasions where geomagnetic storm conditions (K index ≥ 5) are observed at Hartland or Eskdalemuir. However, there are a couple of days that show the maximum K-index of 9 at Lerwick. These days seem to be linked to a solar flare (see e.g. message from 2017 Sep 05 1714 UTC in ftp://ftp.swpc.noaa.gov/pub/alerts/alerts_201709.html). From the results in figures 3-2, 3-9 and 3-10 it can be seen that there is a slightly increased level of error on these days – perhaps due to the ionospheric activity – but it is not out of the ordinary. However, it is possible that at higher latitudes (like Lerwick) the effect was greater and more of an impact on GPS performance would have been observed.

End of Document