AIRSPACE CO-ORDINATION NOTICE Safety and Airspace Regulation Group							
ACN Reference	e:	Version:	Date:	Date of Original			
2022-02-006	0	1.0	31/01/2022	24/01/2022	Civil Aviation Authority		
RADAR CALIBRATION PORTLAND SSR							
			NI	DS			
Subject to NO	TAM	: No					
Date(s) of acti	ivity/\	/alidity:		Times (ALL TIMES UTC)			
04 th February 2	2022 -	– 31 st Decer	nber 2022	08:00 – 18:00			
Vertical Limits	s:			Allocated Mode 3A (SSR):			
4,000ft AMSL -	- 21,0	000ft AGL		0024			
Aircraft Detail	s:	<u></u>		NDS Approved:			
Type: Callsign:	CLB) XXX		Yes – Subject to the conditions in Section 2			
Event Sponsor(s):				Aircraft Operator(s):			
Thales Flight Inspection Service Hangar 3 Teesside International Airport Darlington DL2 1NL 01325 335346				The Operations Officer Thales Flight Inspection Service Hangar 3 Teesside International Airport Darlington DL2 1NL 01325 335346			
ATS Units/ Controlling Agencies:				Geographical Limits:			
Plymouth Mil01752 557808Swanwick ACC – GS West01489 612413Swanwick Mil (78 Sqn) – West01489 612417Western Radar01489 445560Info: Boscombe Down, Bournemouth, Culdrose, Exeter, Yeovilton							
Airspace Reservations:) o l'Aster			
EG D003 EG D004 EG D007A/B EG D008C EG D009A EG D012 EG D013 EG D014 EG D017 EG D021 EG D021 EG D026 AARA 10 (AII) TRA 001	Plym Plym Fowe Plym Wen Lyme Portl Portl Portl Portl Lulw - Sout	houth houth ey houth hbury e Bay (N) e Bay and and and and orth h West	01752 286146 01752 286146 01752 286146 01752 286146 01752 286146 01752 557752 01752 557752 01752 557752 01752 557752 01752 557752 01752 557752 01752 557752 01929 404859 01489 612495 01489 612495				
Departure/Destination Aerodrome(s)				ACN Issued by:			
EGNV				AS3			

SECTION 1: CO-ORDINATION ARRANGEMENTS (GENERAL)

1. The pilot/operator is requested to telephone the ATC authorities on the cover prior to departure in order to notify or update the sortie details including area(s) of operation and planned levels (quoting the ACN Reference). A minimum of 24 hours' notice should be given unless specified in Section 2.

2. There may be other aircraft and/or activities outside Controlled/Regulated Airspace unknown to ATC.

3. The carriage and operation of a serviceable transponder (including Mode 'C') has been specified.

4. The pilot will be responsible for obtaining all necessary ATC clearances and for maintaining R/T contact with appropriate ATC authorities.

5. The pilot/operator will be responsible for obtaining prior clearances to enter any UK Danger Areas affected by the flight profile from the appropriate Range Control Authority unless this is specifically detailed in Section 2.

6. Other Unusual Aerial Activities (UAAs) may be notified to the CAA Safety and Airspace Regulation Group (SARG) and may take place within the airspace encompassed by this flight. The pilot/operator is to ensure that UK Daily NOTAM Nav Warnings are consulted prior to each flight.

7. All flights within Controlled Airspace are subject to the requirements of a Flight Plan in accordance with UK AIP ENR1.10. The ACN Reference should be entered into Field 18 of the Flight Plan together with any relevant 'special handling' codes.

8. Flight prioritisation and Non-Deviating Status is in accordance with the information specified on the ACN Cover. Such status may be afforded to part or all of the flight – see Section 2.

9. Availability of an ATS from Plymouth Military, Swanwick Military (78 Sqn) or Western Radar is subject to unit capacity, priorities and limitations of radar and radio coverage. Minimum pre-flight notification as per UK AIP ENR 1.6 unless otherwise specified in Section 2 of this ACN.

10. The CAA actively encourages the use of Moving map technology in the planning and flying phases of flights to reduce the risk of airspace infringements.

PUBLICATIONS AND CHANGES

11. The activity area may lie within Controlled and Uncontrolled Airspace as well as airspace reserved for military use. Aircrew are to thoroughly familiarise themselves with UK airspace structures and procedures, in particular those laid down within the UK Aeronautical Information Publication (UK AIP), ENR 1.1 and be fully conversant with UK Flight Information Services in accordance with UK CAP 493 (MATS Pt 1).

12. The CAA VFR 1:500,000 and 1:250,000 charts and the UK AIP ENR 5 depict some, but not all aviation activity sites and amendments should also be checked. Please refer to <u>http://www.nats-uk.ead-it.com</u>

13. This ACN details specific coordination essential to the activity taking place and does not remove the need for aircraft operators to comply with national flight planning and notification procedures. Pilots and ANSPs are required to ensure that all related aviation sites are aware of this planned activity and of subsequent changes not captured within this document.

14. The Sponsor or Event Organiser should co-ordinate any changes to this ACN with SARG quoting the ACN Reference at the top of the page.

Airspace Regulation (Utilisation) – AS3 Email: <u>AROps@caa.co.uk</u> Tel: 01293 983880

SECTION 2: CO-ORDINATION ARRANGEMENTS (SPECIFIC)

15. This ACN details the serials required to conduct a calibration of the Monopulse Secondary Search Radar (SSR) at Portland.

16. This ACN replaces ACN 2017-00-0132.

17. **Notification.** The sponsor is to notify the agencies listed on page one of this ACN at least one week prior to undertaking the task. In addition, the pilot is to contact the appropriate agencies at least 4 hours prior to departure to confirm final details and availability of an ATS.

18. The controlling authority is responsible for informing adjacent ATS providers of the details of the flight check, subject to the radial to be flown.

19. **Priority.** This flight has been afforded Non-Deviating Status (NDS) whilst established on a measured run only and within Controlled Airspace (CAS), (*UK AIP ENR 1.1 (4.2) & CAP 493 – Section 1, Ch4, Para 17 refers*,). In order to reduce the impact to other airspace users, the controlling authority may request that the pilot hold, or accept radar vectors in order to make best use of the airspace, or to reduce overall delays. At all other times, flight has been categorised as CAT Z, (*CAP 493 – Section 1, Ch4, Para 10c refers*,) and attracts no priority.

20. **Levels.** The aircraft will be required to operate at the heights listed below. <u>The D Value¹ will then</u> <u>need to be added or subtracted</u>, (value to be confirmed by the sponsor prior to departure), and the <u>converted to a flight level (if above the transitional altitude)</u>. The sponsor is responsible for this conversion and confirm the exact requirement with the controlling agency prior to each run:

- a. 5,560ft AGL² Plymouth Mil, Swanwick Mil, Western Radar, Yeovilton
- b. 10,560ft AGL Plymouth Mil, Swanwick Mil
- c. 20,560ft AGL Plymouth Mil, Swanwick Mil

21. **Radials.** The radials required by the aircraft are subject to wind speed and direction and may vary. A single radial will be chosen between the following options:

a. 230°T to 270°T

22. The aircraft is required to conduct up to eight runs at each level, operating between 40nm and 80nm from the radar head.

23. **Orbits.** Up to two, 10nm orbits will be required, flown at 4,000ft AMSL. The orbits can be flown either clockwise or anti-clockwise.

24. **Air Traffic Service (ATS) Provision – CAS.** Access to controlled airspace is subject to the prevailing traffic situation and controller workload. The pilot is responsible for obtaining a clearance to enter controlled airspace prior to penetration.

25. **ATS Provision – Outside CAS.** The calibration area is within the coverage of the following units:

a.	Plymouth Mil	124.150 MHz
b.	Swanwick Mil	135.150 MHz
c.	Western Radar	132.300 MHz

¹ D' Values are corrected from ICAN standard atmosphere to actual conditions, thus aircraft on inbound leg may be unable to maintain whole Flight Levels

² AGL in this instance relates to the height above the radar antenna – Elevation 560ft

26. Availability of an ATS service from a unit is not guaranteed, is subject to controller availability, unit workload and possible reduced hours of operations (due to COVID-19 or operations reasons). Amendments to the published hours of availability, as listed in the UK AIP ENR 1.6 – Para 4.1, AD2 or UK Military AIP, shall be notified via NOTAM.

27. **ATS Provision above FL100.** This service is available to all aircraft flying outside Controlled Airspace in the UK FIRs between FL 100 and FL 190, and within active TRAs and is subject to Unit capacity. The Units providing this service together with their boundaries are depicted within the UK AIP on the chart ENR 6-12. ENR 1.6 (4.2) lists their hours of operation, the RTF operating frequency on which this service is normally provided and a telephone number for pre-flight contact. A FPL should be filed and include the following addresses:

- a. EGZYOATT Swanwick Mil (78 Sqn)
- b. EGTTZFZC Western Radar

28. Amendments to the published hours of availability, as listed in the UK AIP ENR 1.6 – Para 4.2, shall be notified via NOTAM.

29. Between the hours of 18:00 to 08:00 (local time) on a weekday, at any time on a weekend or during a UK public holiday, Swanwick Mil (78 Sqn) require at least two weeks prior notice in order to obtain an ATS in support of this task.

30. **Danger Areas (DAs).** Access to any DA is subject to military requirements and access is not guaranteed. The sponsor is to engage with the DA Authority at the earliest opportunity to coordinate access, noting that access may only be possible outside notified operating hours. For the South Coast DAs, it is strongly suggested book access via the controlling authority, before Thursday of the proceeding week. For bookings inside this timeframe, please contact 01752 557550.

31. **Temporary Reserved Area (TRA).** The sponsor is responsible for complying with the requirements for access to any TRA iaw the UK AIP – ENR 1.1 (Para 5.1.5).

SECTION 3

Area of Operation

32. Charts highlighting the various area of operation are shown below. These are for illustrative purposes only and not for operational planning.



Chart 1 – Overview

Chart 2 - 230 ° - 270°



Chart 3 – Orbit

